



## **COHESIVE RUBBER TAPE, CR**

## FOR TEMPORARY COVERING AND MOISTURE SEAL DURING TELEPHONE CABLE SPLICING.

Technical Data Sheet October 2017

## Description and Features

Plymouth Cohesive rubber tape, CR, consists of one soft, uncured layer bonded to a cured resistant layer which provides mechanical strength. Can be squeezed together to form an airtight, gas proof seal.

Two-ply blanket tape that makes a perfect temporary covering and moisture seal while it is splicing, repairing or jointing insulated cable, or working on temporary gas-filled splices.

- High Tensile Strength
- Abrasion resistant black layer
- Excellent Cohesion
- Make it easy to create fast, durable, air-tight and gas proof seals by hand

Materials	Backing Adhesive Black White Cured Uncured		Stand	Standard Size Width x Length	
			Width		
			711 mm x 6,1 m (28 in. x 20 ft.)		
	rubber	Rubber Other sizes availab		lable upon request	
Technical Properties	Characterist	ic	Typical Value	Test Method	
-	Thickness, (m	im)	1,27	ASTM D 4325	
	Breaking strer		7,5	ASTM D 412	
	Elongation at	• · /	600	ASTM D 412	
	Cohesion	( )	Excellent		
			(positively disrupted)		
	Dielectric Stren	gth, (kV/mm)	24	ASTM D 149	
Recommended Uses	For a temporary cover and moisture Seal during a splicing or repairing of insulated telephone cable.				
Storage	In original packaging, placed in horizontal position under cover and temperature between 5°C and 35 °C.				
Shelf Life	24 months from date of manufacture.				

Data in table represents average test results and are not to be used for specification purpose. The product users should make their own tests to determine the products' suitability for the intended use.

LIMITED WARRANTY: Plymouth warrants that its Product will substantially conform to that products written specifications for a period of one (1) year from the date of shipment, (Unless provided otherwise). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/fits intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first compiled with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (rev. 1/2017-2019)