



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE1474 Integrated Circuit FM IF Amp

Features:

- High Sensitivity: $V_{IN(lim)} = 78\text{dB}\mu\text{V}$
- Wide Frequency Capability
- Regulated Voltage Output
- Wide Operating Supply Voltage Range: $V_{CC} = 8\text{V}$ to 16V

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC}	16V
Pin 5 Output Current, I_5	13mA
Power Dissipation (Note 1), P_D	500mW
Operating Temperature Range, T_{opr}	-25° to +75°C
Storage Temperature Range, T_{stg}	-55° to +150°C

Note 1. Derated above $T_A = +25^\circ\text{C}$ in the proportion of $4\text{mW}/^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Supply Current	I_{CC}		6.4	9.4	12.4	mA
Pin 6 Current	I_6		1.3	2.0	2.6	mA
Pin 5 Voltage	V_5		5.7	—	6.9	V
Voltage Gain	G_V	$f = 10.7\text{MHz}, V_{in} = 60\text{dB}\mu\text{V}$	31	34	37	dB
Input Limiting Voltage	$V_{IN(lim)}$	$f = 10.7\text{MHz}, V_O = -3\text{dB}$	—	78	—	$\text{dB}\mu\text{V}$
Parallel Input Resistance	r_{ip}	$f = 10.7\text{MHz}$	—	8	—	$\text{k}\Omega$
Parallel Input Capacitance	C_{ip}		—	5	—	pF
Parallel Output Resistance	r_{op}		—	200	—	$\text{k}\Omega$
Parallel Output Capacitance	C_{op}		—	2.5	—	pF

Pin Connection Diagram

