

NTE1829 Integrated Circuit Quad Transistor Array, 5kΩ

Features:

- 4 Circuits
- Output Current: $I_C = 50\text{mA}$
- Breakdown Voltage: $V_{CEO} = 24\text{V}$
- Built-In Base Current Limiting Resistor

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Collector-Base Voltage, V_{CBO}	50V
Collector-Emitter Voltage, V_{CEO}	24V
Collector Substrate Voltage, V_{CIO}	50V
Collector Current, I_C	50mA
Input Voltage, V_1	-0.5V to 50V
Collector Power Dissipation (Per Transistor), P_C	250mW
Power Dissipation, P_D	1000mW
Operating Ambient Temperature Range, T_{opr}	-30° to +75°C
Storage Temperature Range, T_{stg}	-55° to +150°C

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector-Base Voltage	V_{CBO}	$I_C = 10\mu\text{A}, I_E = 0$	50	-	-	V
Collector-Emitter Voltage	V_{CEO}	$I_C = 1\text{mA}, I_B = 0$	24	-	-	V
Collector Leakage Current	I_{CEO}	$V_{CE} = 10\text{V}, R_{BE} = \infty$	-	-	1	μA
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 5\text{mA}, I_1 = 0.55\text{mA}$	-	0.1	0.2	V
		$I_C = 25\text{mA}, I_1 = 2.25\text{mA}$	-	0.3	0.4	V
Input Voltage	V_1	$V_{CE} = 300\text{mV}, I_C = 5\text{mA}$	-	1.2	2.2	V
		$V_{CE} = 500\text{mV}, I_C = 25\text{mA}$	-	3.0	5.1	V
Input Current	I_1	$I_C = 5\text{mA}, V_1 = 5\text{V}$	-	0.85	1.2	mA
		$I_C = 25\text{mA}, V_1 = 15\text{V}$	-	2.9	4.2	mA

Pin Connection Diagram
(Front View)

