



ELECTRONICS, INC.  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089  
<http://www.nteinc.com>

## NTE1861 Integrated Circuit TV Video IF Processor

**Features:**

- PLL True Synchronous Detector Incorporates VCO
- Quadrature Sound FM Detector
- AGC Defeat Terminal (Pin 20)

**Absolute Maximum Ratings:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Supply Voltage, $V_{CC}$ .....	13.8V
Circuit Voltage	
$V_{5-1,14,21}$ .....	$V_{4,12-1,14,21}$ to 0V
$V_{6-1,14,21}$ .....	$V_{4,12-1,14,21}$ to 0V
$V_{7-1, 14,21}$ .....	$V_{4,12-1,14,21}$ to 0V
$V_{10-1,14,21}$ .....	$V_{4,12-1,14,21}$ to 0V
$V_{18-1,14,21}$ .....	$V_{4,12-1,14,21}$ to 0V
$V_{25-1,14,21}$ .....	8.0V to 0V
Circuit Current	
$I_{17}$ .....	-7mA to +0.5mA
$I_{19}$ .....	-7mA to +0.5mA
$I_{26}$ .....	-5mA to +0.5mA
Power Dissipation ( $T_A = +70^\circ\text{C}$ ), $P_D$ .....	1300mW
Operating Ambient Temperature Range, $T_{opr}$ .....	-20° to +70°C
Storage Temperature Range, $T_{stg}$ .....	-55° to +150°C

**Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
<b>IF Amplifier • Detection • AGC • AFC Circuit</b>						
Video Detector Output	$V_O$	$f = 58.75\text{MHz}$ , $V_i = 80\text{dB}\mu$ , $m = 87.5\%$	1.8	2.1	2.4	$V_{p-p}$
Input Sensitivity	$S_{(IN)}$	$V_O = -3\text{dB}$	49	53	57	$\text{dB}\mu$
Max. Allowable Input	$V_{I(max)}$		103	108	-	$\text{dB}\mu$
Differential Gain	DG	$f = 58.75\text{MHz}$ , $V_i = 80\text{dB}\mu$ , $m = 87.5\%$	-	2	6	%
Differential Phase	DP	$f = 58.75\text{MHz}$ , $V_i = 80\text{dB}\mu$ , $m = 87.5\%$	-	2	5	deg
Frequency Characteristics	$f_c$	$V_O = -3\text{dB}$	4.5	5	6	MHz
RF AGC Gain	$G_{RFAGC}$	$f = 10\text{kHz}$ , $V_i = 10\text{mV}$	40	44	48	dB
AFC Phase Det. Sensitivity	$\mu$	$R_L = 68\Omega/82\text{k}\Omega$	30	40	60	$\text{mV/kHz}$
AFC Center Voltage	$V_{10}$	$R_L = 68\text{k}\Omega/82\text{k}\Omega$	4.2	6.5	8.2	V
<b>VCO APC Circuit</b>						

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
VCO Max. Variable Range	$\Delta f_{V(1)}$	$V_{13} = 2V$	+0.85	+1.5	+2.5	MHz
	$\Delta f_{V(2)}$	$V_{13} = 3V$	-4.0	-2.4	-1.4	MHz
VCO Control Sensitivity	$\beta$		3	4.5	6	kHz/mV
APC Pull-In Range	$f_{APC(1)}$		+0.85	+1.5	+2.5	MHz
	$f_{APC(2)}$		-3.5	-2.5	-1.6	MHz
<b>SIF Circuit</b>						
Total Detector Output	$V_O$	$f_o = 4.5\text{MHz}, f_m = 400\text{Hz}, \Delta f = \pm 25\text{kHz}, V_i = 100V_{ms}$	400	500	600	$mV_{rms}$
Input Limiting Voltage	$V_{i(lim)}$	$f_o = 4.5\text{MHz}, f_m = 400\text{Hz}$	-	36	40	$\text{dB}\mu$
<b>DC Characteristics</b>						
Circuit Current	$I_4+I_{12}$		50	70	90	mA

### Pin Connection Diagram

