



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE452 Silicon N-Channel JFET Transistor VHF Amplifier, Mixer TO72 Type Package

Description:

The NTE452 is a silicon, N-channel junction field effect transistor (JFET) in a TO72 type package designed to be used in the depletion mode in VHF/UHF amplifiers.

Absolute Maximum Ratings:

Drain-Source Voltage, V_{DS}	30V
Drain-Gate Voltage, V_{DG}	35V
Gate-Source Voltage, V_{GS}	30V
Gate Current, I_G	10mA
Total Device Dissipation ($T_A = +25^\circ\text{C}$), P_D	300mW
Derate Above 25°C	1.71mW/ $^\circ\text{C}$
Operating Junction Temperature Range, T_J	-65° to $+175^\circ\text{C}$
Storage Temperature Range, T_{stg}	-65° to $+175^\circ\text{C}$

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF Characteristics						
Gate-Source Breakdown Voltage	$V_{(BR)GSS}$	$I_G = 1^\circ\text{s}, V_{DS} = 0$	30	-	-	V
Gate Reverse Current	I_{GSS}	$V_{GS} = 20\text{V}, V_{DS} = 0$	-	-	100	pA
		$V_{GS} = 20\text{V}, V_{DS} = 0, T_A = +150^\circ\text{C}$	-	-	200	pA
Gate-Source Cutoff Voltage	$V_{GS(off)}$	$I_D = 1\text{nA}, V_{DS} = 15\text{V}$	-	-	6	V
Gate-Source Voltage	V_{GS}	$I_D = 0.5\text{mA}, V_{DS} = 15\text{V}$	1.0	-	5.5	V
Gate-Source Forward Voltage	$V_{GS(f)}$	$I_G = 1\text{mA}, V_{DS} = 0$	-	-	1.0	V
ON Characteristics (Note 1)						
Zero-Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 15\text{V}, V_{GS} = 0$	5	-	15	mA
Small-Signal Characteristics						
Forward Transfer Admittance	$ Y_{fs} $	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 1\text{kHz}, \text{Note 1}$	4500	-	7500	$^\circ\text{mhos}$
Real Part of Forward Transfer Admittance	$Y_{fs(real)}$	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 400\text{MHz}$	4000	-	-	$^\circ\text{mhos}$

Note 1. Pulse Test: Pulse Width $\leq 300^\circ\text{s}$, Duty Cycle $\leq 1\%$.

Electrical Characteristics (Cont'd): ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Small-Signal Characteristics (Cont'd)						
Real Part of Input Admittance	$Y_{is(\text{real})}$	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 100\text{MHz}$	-	-	100	$^\circ\text{mhos}$
		$V_{DS} = 15\text{V}, V_{GS} = 0, f = 400\text{MHz}$	-	-	1000	$^\circ\text{mhos}$
Output Admittance	$ Y_{os} $	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 1\text{kHz}$	-	-	50	$^\circ\text{mhos}$
Real Part of Output Admittance	$Y_{os(\text{real})}$	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 100\text{MHz}$	-	-	75	$^\circ\text{mhos}$
		$V_{DS} = 15\text{V}, V_{GS} = 0, f = 400\text{MHz}$	-	-	100	$^\circ\text{mhos}$
Imaginary Part of Input Admittance	$Y_{is(\text{imag})}$	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 100\text{MHz}$	-	-	2500	$^\circ\text{mhos}$
		$V_{DS} = 15\text{V}, V_{GS} = 0, f = 400\text{MHz}$	-	-	10k	$^\circ\text{mhos}$
Imaginary Part of Output Admittance	$Y_{os(\text{imag})}$	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 100\text{MHz}$	-	-	1000	$^\circ\text{mhos}$
		$V_{DS} = 15\text{V}, V_{GS} = 0, f = 400\text{MHz}$	-	-	4000	$^\circ\text{mhos}$
Input Capacitance	C_{iss}	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 1\text{MHz}$	-	-	4.0	pF
Reverse Transfer Capacitance	C_{rss}	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 1\text{MHz}$	-	-	0.8	pF
Common-Source Output Capacitance	C_{oss}	$V_{DS} = 15\text{V}, V_{GS} = 0, f = 1\text{MHz}$	-	-	2.0	pF
Functional Characteristics						
Noise Figure	NF	$V_{DS} = 15\text{V}, I_D = 5\text{mA}, R_g \leq 1000\Omega, f = 100\text{MHz}$	-	-	2.0	dB
		$V_{DS} = 15\text{V}, I_D = 5\text{mA}, R_g \leq 1000\Omega, f = 400\text{MHz}$	-	-	4.0	dB
Small-Signal Power Gain Common-Source	G_{ps}	$V_{DS} = 15\text{V}, I_D = 5\text{mA}, f = 100\text{MHz}$	18	-	-	dB
		$V_{DS} = 15\text{V}, I_D = 5\text{mA}, f = 400\text{MHz}$	10	-	-	dB

