



ELECTRONICS, INC.

44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE7010 Integrated Circuit Single Chip NTSC Color TV Processor ^w/OSD Interface

Description:

The NTE7010 combines all the functions required for an NTSC color TV system in a 54-Lead DIP type package. This device includes PIF/SIF circuits, video/chroma/deflection circuits, chroma band pass filters, red and green OSD interfaces, and 1 channel audio video switches.

PIF Circuits

- 3-Stage Variable-Gain PIF Amplification Stage
- High-Speed Response ACC with Dual Time Constants (Peak AGC)
- Single End AFT Output with Defeat Function
- RF Delay AGC Output (Reverse AGC)
- Sync. Negative Detected Video Output Polarity
- Internal Black/White Noise Inverter

SIF Circuits

- 3-Stage Limiter Amplification Stage
- Quadrature FM Detector Circuit with Sound Mute Function
- 1 Channel External Audio Input
- High-Performance Electronic Attenuator Circuit
- Preamplifier Circuit

Video Circuit

- 2nd Order-Differential-Type Picture Sharpness Circuit (DC Control)
- Contrast Control with Unicolor Function
- Brightness Control with Pedestal Clamping Circuit (Variable DC Restoration Ratio)
- External Video Input

Chroma Circuit

- Internal $\frac{1}{2} f_{sc}$ Trap
- Internal Band Pass Filter
- ACC Circuit
- Color Control Circuit
- Unicolor Control Circuit
- Color Differential Output
- Tint Control Circuit
- Adjustment-Free APC Circuit

Deflection Circuits

- High-Performance Sync Separation Circuit
- Adjustment-Free Horizontal Oscillation Circuit
- Stable Vertical Synchronization
- Sawtooth-Type AFC (Internal Sawtooth Wave Generator)
- Horizontal Predrive Output
- X-Ray Protection Circuit
- Vertical NFB Amplification Circuit

OSD Interface (R, G Inputs)

- Directly Driven by μ -computer

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Power Supply Voltage, V_{CC}	13V
Internal Pin Voltage, V_{in}	GND -0.3V to $V_{CC} +0.3\text{V}$
Input Signal Amplitude, e_{in}	$4V_{P-P}$
Power Dissipation, P_D	1.92W
Derate Above 25°C	$15.3\text{mW}/^\circ\text{C}$
Operating Temperature Range, T_{opr}	-20° to $+65^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55° to $+150^\circ\text{C}$

Note 1. **CAUTION!** This device is easily damaged by high static voltage or electric fields so extreme care should be used when handling.



