



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089

NTE7060 **Integrated Circuit** **NTSC Single Chip Color TV Signal Processor**

Description:

The NTE7060 is an integrated circuit in a 52-Lead DIP type package that combines all of the signal (VIF, SIF, Video, Color and Synchronous Signal) processing circuits in NTSC color TV onto one chip.

Features:

- VIF Circuit using PLL Complete Synchronous Detection
- Audio External Input Pin and Volume Adjusting Circuit Built-In
- Y Delay Line Built-In and Y Delay Line Switchable
- Block Level Compensation Circuit Built-In
- 3.58MHz BPF Built-In
- APC Killer Filter Built-In (No Adjustment of ACP)
- On-Screen Pin Attached (Only for Green and Other Output Blanking)
- Compatible with S-VHS System (3.58MHz ON/OFF Switching)
- No Adjustment of Horizontal/Vertical Oscillation Frequency
- Horizontal Synchronous Lock Detecting Pin Attached
- Service Switch Circuit Built-In (Vertical Out Stop, Y Out Blanking)
- Y Output is Black Level when No Synchronous Signal is Input

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC1}	12V
Supply Current (I_{43}), I_{CC}	82mA
Supply Current (I_9), I_{CC}	30mA
Supply Current (I_{32-19}), I_{CC}	61mA
Power Dissipation ($T_A = +70^\circ\text{C}$), P_D	1.3mW
Operating Ambient Temperature Range, T_{opr}	-20° to $+70^\circ\text{C}$
Storage Temperature Range, T_{stg}	-55° to $+150^\circ\text{C}$

Recommended Operating Range: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Operating Supply Voltage Range, V_{CC1}	8.1V to 9.9V
Operating Supply Voltage Range, $V_{CC3,4}$	4.5V to 5.5V

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
VIF Section						
Video Detection Output	V_{O21}	$M = 87.5\%$, $V_{in} = 80\text{dB}\mu$	1.75	2.0	2.25	V_{P-P}
Video Frequency Characteristics	f_C	-3dB Frequency for 1MHz Detection Output	4.0	5.5	-	MHz
VCO Oscillator Sensitivity	β	$\Delta V_{20} = 0.2\text{V}$ (DC: About 2V)	3.0	4.3	6.5	kHz/mV
RF AGC Sensitivity	G_{RF}	Difference in Input Level of $V_{33} = 1\text{V} \rightarrow 7\text{V}$	-	1.5	3.0	dB
AFC Phase Detector Sensitivity	μ_{AFC}	$R_L = 100\text{k}\Omega/100\text{k}\Omega$	25	40	55	mV/kHz
SIF Section						
Audio Detection Output	V_{O27}	$f_O = 4.5\text{MHz}$, $V_{in} = 100\text{dB}\mu$, $\Delta f = \pm 25\text{kHz}$, $f_m = 1\text{kHz}$	125	155	185	mV_{rms}
Audio Output	V_{O28}		410	530	650	mV_{rms}
Video Signal Processing Section						
Video Voltage Gain	A_V	Input: $f = 1\text{MHz}$, $0.2V_{P-P}$, Contrast VR: Max	7.6	9.3	12.2	Times
Video Frequency Characteristics	f_{YC}	Picture Quality VR: Min., 3dB Down from $f = 1\text{MHz}$	4.5	5.5	-	MHz
Brightness Oscillator Sensitivity	BR	Bright VR = 7.5V to 8V	-4.5	-3.6	-2.7	Times
Chroma Signal Processing Section						
Color Difference Output (Typ.)	e_{O1B}	B-Y Color Bar Signal Color VR: 3.3V, Contrast VR: 5V	2.3	3.0	3.7	V_{P-P}
Color Difference Output (Max.)	e_{O2B}	B-Y Color Bar Signal Color VR: 5V, Contrast VR: 5V	3.7	4.7	5.7	V_{P-P}
ACC Characteristics	ACC	Burst 200 \rightarrow 400mV $_{P-P}$	0.9	1.0	1.1	Times
		Burst 200 \rightarrow 20mV $_{P-P}$	0.5	0.7	1.0	Times
Demodulator Output Ratio	R/B	Color Bar Signal (Burst 200mV $_{P-P}$)	0.72	0.96	1.2	Times
	G/B		0.22	0.31	0.39	Times
Demodulator Angle R	$\angle R$		89	104	119	Deg.
Demodulator Angle G	$\angle G$		225	240	255	Deg.
Color Killer Tolerance	e_K		Color Bar Signal Burst 200mV $_{P-P} = 0\text{dB}$	-55	-42	-30
Synchronous Signal Processing Section						
Horizontal Natural Oscillation Frequency	f_{HO}	Output frequency of Pin4	15.45	15.75	16.05	kHz
Horizontal Pull-In Range	f_{PH}		15.25	-	16.25	kHz

Pin Connection Diagram

	1		52	
GND				Sharpness
Vertical Output	2		51	Pedestal Blank
X-Ray Protect	3		50	Brightness Adjustment
Horizontal Output	4		49	Black Level Compensation
GND	5		48	Y Output
Horizontal Oscillation (VCO)	6		47	On-Screen Input (G-Y)
Horizontal AFC Output	7		46	B-Y Output
FBP Sawtooth Input	8		45	G-Y Output
V _{CC2} (6.1V)	9		44	R-Y Output
Flyback Pulse Input	10		43	V _{CC1} (9V)
Sync Separator Input	11		42	Tint Adjustment
Vertical Sync Input	12		41	Color Saturation Adjustment
Y Input	13		40	Contrast Adjustment/Service SW
Vertical Sync Output	14		39	3.58MHz Oscillation
Chroma Input	15		38	ACC Detection Filter
Horizontal AFC Lock Detect	16		37	GND
VCO Coil Pin	17		36	VIF Input
VCO Coil Pin	18		35	VIF Input
V _{CC4} (5V)	19		34	V _{CC3} (5V)
APC Filter	20		33	RF AGC Output
Video Detection Output	21		32	IF AGC Output/AV Switching
AFC Tank Circuit	22		31	RF AGC Delay Adjustment
AFC Tank Circuit	23		30	SIF Coil
AFC Output	24		29	SIF Coil
SIF Input/Volume Adjustment	25		28	Audio Output
Audio Feedback	26		27	Audio Detection Output/External Audio Input

