



ELECTRONICS, INC.

44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089

<http://www.nteinc.com>

NTE725 Integrated Circuit Dual Low Noise Preamp/OP Amp

Description:

The NTE725 consists of two identical high-gain operational amplifiers constructed on a single chip. These 3-stage amplifiers use Class A PNP transistor output stages with uncommitted collectors. This enables a variety of loads to be employed for general purpose applications from DC to 10MHz, where two high performance operation amplifiers are required. In addition, the outputs may be wired-OR for use as a dual comparator or they may function as diodes in low threshold rectifying circuits such as absolute value amplifiers, peak detectors, etc.

Features:

- Single or Dual Supply Operation
- Low Power Consumption
- High Gain
- Large Common Mode Range: +11V, -13V
- Excellent Gain Stability vs. Supply Voltage
- No Latch-Up
- Output Short Circuit Protected

Absolute Maximum Ratings:

Supply Voltage	±18V
Internal Power Dissipation	650mW
Differential Input Voltage	±5V
Input Voltage (Note 1)	±15V
Output Short Circuit Duration (T _A = +25°C, Note 2)	30sec
Operating Temperature Range	0° to +70°C
Storage Temperature Range	-55° to +125°C
Lead temperature (During Soldering, 60sec)	+260°C

Note 1. For supply voltages less than ±15V, the absolute maximum input voltage is equal to the supply voltage.

Note 2. Short circuit may be to GND or either supply.

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_+ = \pm 15\text{V}$, $R_L = 5\text{k}\Omega$ to Pin7 unless otherwise specified)

Parameter	Test Conditions	Min	Typ	Max	Unit
Input Offset Voltage	$R_S = 200\Omega$	-	1.0	6.0	mV
	$V_+ = \pm 4\text{V}$, $R_L = 10\text{k}\Omega$ to Pin7, $R_S = 200\Omega$	-	1.0	6.0	mV
Input Offset Current		-	50	1000	nA
	$V_+ = \pm 4\text{V}$, $R_L = 10\text{k}\Omega$ to Pin7	-	50	1000	nA
Input Bias Current		-	0.3	2.0	μA
	$V_+ = \pm 4\text{V}$, $R_L = 10\text{k}\Omega$ to Pin7	-	300	-	μA
Input Resistance		37	150	-	$\text{k}\Omega$
Large Signal Voltage Gain	$V_{\text{OUT}} = \pm 10\text{V}$	6.5k	20k	-	V/V
	$V_+ = \pm 4\text{V}$, $R_L = 10\text{k}\Omega$ to Pin7, $V_{\text{OUT}} = \pm 2\text{V}$	2.5k	15k	-	V/V
Positive Output Voltage Swing		+12	+13	-	V
	$V_+ = \pm 4\text{V}$, $R_L = 10\text{k}\Omega$ to Pin7	+2.5	+2.8	-	V
Negative Output Voltage Swing		-14	-15	-	V
	$V_+ = \pm 4\text{V}$, $R_L = 10\text{k}\Omega$ to Pin7	-3.6	-4.0	-	V
Output Resistance	$f = 1\text{kHz}$	-	5.0	-	$\text{k}\Omega$
Common Mode Rejection Ratio	$R_S = 200\Omega$, $V_{\text{IN}} = +11.5\text{v}$ to -13.5V	70	90	-	dB
Supply Voltage Rejection Ratio	$R_S = 200\Omega$	-	50	-	$\mu\text{V/V}$
Input Voltage Range		-10	-	+11	V
Internal Power Dissipation	$V_+ = \pm 4\text{V}$, $R_L = 10\text{k}\Omega$ to Pin7, $V_{\text{OUT}} = 0$	-	20	-	mW
Supply Current	$V_{\text{OUT}} = 0$	-	9	14	mA
	$V_+ = \pm 4\text{V}$, $R_L = 10\text{k}\Omega$ to Pin7, $V_{\text{OUT}} = 0$	-	2.5	-	mA
Broadband Noise Figure	$R_S = 10\text{k}\Omega$, BW = 10Hz to 10kHz	-	2.0	-	dB
Turn-On Delay	Open Loop, $V_{\text{IN}} = \pm 20\text{mV}$	-	0.2	-	μs
Turn-Off Delay	Open Loop, $V_{\text{IN}} = \pm 20\text{mV}$	-	0.3	-	μs
Slew Rate (Unity Gain)	$C_1 = 0.02\mu\text{F}$, $R_1 = 33\Omega$, $C_2 = 10\text{pF}$	-	1.0	-	$\text{V}/\mu\text{s}$
Channel Separation	$R_S = 1\text{k}\Omega$, $f = 10\text{kHz}$	-	140	-	dB

Pin Connection Diagram



