



**ELECTRONICS, INC.**  
 44 FARRAND STREET  
 BLOOMFIELD, NJ 07003  
 (973) 748-5089

## NTE941 Integrated Circuit Operational Amplifier

**Description:**

The NTE941 is a general purpose operational amplifier in an 8-Lead TO5 Metal Can type package and offers many features which make its application nearly foolproof: overload protection on the input and output, no latch-up when the common mode range is exceeded, as well as freedom from oscillators.

**Absolute Maximum Ratings:**

Supply Voltage, $V_S$ .....	$\pm 18V$
Differential Input Voltage, $V_{ID}$ .....	$\pm 30V$
Common Mode Input Voltage (Note 2), $V_{ICM}$ .....	$\pm 15V$
Power Dissipation (Note 1), $P_D$ .....	500mW
Output Short-Circuit Duration, $t_S$ .....	Continuous
Junction Temperature, $T_J$ .....	+100°C
Operating Temperature Range, $T_{opr}$ .....	0° to +70°C
Storage Temperature Range, $T_{stg}$ .....	-65° to +150°C
Lead Temperature (During Soldering, 10sec), $T_L$ .....	+300°C
Thermal Resistance, Junction-to-Ambient, $R_{thJA}$ .....	+150°C/W
Thermal Resistance, Junction-to-Case, $R_{thJC}$ .....	+80°C/W

Note 1. For operation at elevated temperatures, these devices must be derated based on thermal resistance, and  $T_J \text{ Max } (T_J = T_A + (R_{thJA} P_D))$ .

Note 2. For supply voltage less than  $\pm 15V$ , the absolute maximum input voltage is equal to the supply voltage.

**Electrical Characteristics:** ( $V_S = \pm 15V$ ,  $0^\circ \leq T_A \leq +70^\circ C$  unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit	
Input Offset Voltage	$V_{IO}$	$R_S \leq 10k\Omega$	$T_A = +25^\circ C$	-	2.0	6.0	mV
				-	-	7.5	mV
Input Offset Voltage Adjustment Range	$V_{IOR}$	$V_S = \pm 20V$ , $T_A = +25^\circ C$	-	$\pm 15$	-	V	
Input Offset Current	$I_{IO}$	$T_A = +25^\circ C$	-	20	200	nA	
			-	-	300	nA	
Input Bias Current	$I_{IB}$	$T_A = +25^\circ C$	-	80	500	nA	
			-	-	0.8	$\mu A$	
Input Resistance	$r_i$	$V_S = \pm 20V$ , $T_A = +25^\circ C$	0.3	2.0	-	$M\Omega$	
Common Mode Input Voltage Range	$V_{ICR}$	$T_A = +25^\circ C$	-	$\pm 12$	$\pm 13$	V	
Large Signal Voltage Gain	$A_V$	$V_O = \pm 10V$ , $R_L \geq 2k\Omega$	$T_A = +25^\circ C$	20	200	-	V/mV
				15	-	-	V/mV
Output Voltage Swing	$V_O$	$R_L \geq 10k\Omega$		$\pm 12$	$\pm 14$	-	V
		$R_L \geq 2k\Omega$		$\pm 10$	$\pm 13$	-	V
Output Short-Circuit Current	$I_{OS}$	$T_A = +25^\circ C$	-	25	-	mA	
Common-Mode Rejection Ratio	CMRR	$R_S \leq 10k\Omega$ , $V_{CM} = \pm 12V$	70	90	-	dB	
Supply Voltage Rejection Ratio	PSRR	$V_S = \pm 20V$ to $\pm 5V$ , $R_S \leq 10k\Omega$	77	96	-	dB	
Transient Response Rise Time	$t_{TLH}$	$T_A = +25^\circ C$ , Unity Gain	-	0.3	-	$\mu s$	
Transient Response Overshoot	os		-	5	-	%	
Transient Response Slew Rate	SR		-	0.5	-	V/ $\mu s$	
Supply Current	$I_D$	$T_A = +25^\circ C$	-	1.7	2.8	mA	
Power Consumption	$P_C$	$T_A = +25^\circ C$	-	50	85	mW	



