# Barristo Enterprises, Inc., dba SureHold<sub>®</sub>

## SAFETY DATA SHEET

## Low Odor, Low Blooming Cyanoacrylate Adhesive

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product Name Low Odor, Low Blooming Cyanoacrylate Adhesive

Part Number SH-201

Company Barristo Enterprises, Inc. dba SureHold

3717 N Ravenswood Avenue, Suite 243

Chicago, IL 60613 info@surehold.com www.surehold.com

Telephone + 773-472-8592; Toll Free 800-881-4495

Fax + 773-525-1750

Emergency telephone

number 800-881-4495

#### 2. HAZARDS IDENTIFICATION

Main hazards Warning: Bonds skin in seconds. May cause eye and respiratory irritation. Combustible

liquid and vapor.

Primary Routes of Entry

nary routes of Entry

Signs and Symptom of Exposure

Skin, Eyes, Inhalation

<u>Inhalation</u> Exposure to vapor above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and feeling of tightness in the chest. <u>Skin contact</u> Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reactions but due to the rapid polymerization, allergic response is rare. Cyanoacrylates generate heat on polymerization, so very large amounts will burn the skin. The solidified does not present a health problem when

**Eye contact** Irritating to eyes. Will bond eyelids. Will cause excessive tearing.

<u>Ingestion</u> Not expected to be harmful by ingestion. Rapid polymerization and bonds in mouth. It is very difficult to swallow.

3. COMPOSITION / INFORMATION ON INGREDIENTS

bonded to the skin.

Component Conc. CAS ACGIH;TLV-TWA OSHA PEL Methoxy-ethyl Cyanoacrylate 70-100% 27816-23-5 0.2ppmTWA None

#### 4. FIRST AID MEASURES

Skin contact Do not pull bonded skin apart. Soak in warm, soapy water. Gently pry apart using a

blunt instrument. If skin is burned because of large amounts of product, get medical

attention.

Eye contact Immediately flush with plenty of water. Get medical attention. If eyelids are bonded

shut, release eyelashes first with a wet pad and warm water. Do not force eye open. Cyanoacrylates will bond to the eye, tearing will help de-bond the adhesive. Keep eye covered until de-bonding is complete, usually within 3 days. Solid particles from the

polymerized product can cause abrasive damage. Get medical attention.

Inhalation Remove to fresh air. If symptoms persist, get medical attention.

Ingestion Ensure that breathing airways are not obstructed. The product will polymerize rapidly

and bond to the mouth making swallowing extremely difficult. Usually any solidified product will separate after a few hours. Prevent any further swallowing of the separated

material.

#### SUREHOLD. Low Odor, Low Blooming Cyanoacrylate Adhesive, SH-201

Revision 1 Revision Date 15-Jan-2015

5. FIRE FIGHTING MEASURES

Extinguishing media Carbon dioxide, foam and dry chemical.

Hazardous Product of

Trace amounts of toxic and irritating fumes.

Combustion

Special Firefighting Firefighters should wear positive pressure self-contained breathing apparatus.

**Procedures** 

Unusual Fire/Explosion None

Hazards

Lower Explosive Limit Not determined Upper Explosive Limit Not determined

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions Prevent spill from entering drains or open waters. Ventilate area.

Cleanup methods: Do not use cloth for clean-up. Flood with water to complete polymerization and scrape

up the polymer. Solid material can be disposed of as a non-hazardous waste.

7. HANDLING AND STORAGE

Handling Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mists. Wash

thoroughly after handling. Avoid contact with fabric and paper goods. Contact with these may cause rapid polymerization that can generate smoke and strong irritating

vapors and can cause thermal burns.

Storage Keep in a cool, well-ventilated area away from heat, sparks and open flame. Keep

container tightly closed until ready for use.

Incompatible products No special restrictions on storage with other products

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls If general ventilation is insufficient to maintain vapor concentration below established

exposure limits, use positive downdraft exhaust ventilation.

Skin protection Use Nitrile gloves and aprons to prevent contact. DO NOT USE PVC, nylon or cotton.

Eye/face protection Safety glasses with side shields or chemical splash goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear colorless to straw, Liquid.

Odor Negligible.

Boiling point / range Greater than 150°C

Flash point 80°C to more than 93°C Method: Tag Closed Cup

pH Not applicable Melting point / range Not determined

Solubility in Water Polymerizes in the presence of water

Specific Gravity 1.10 @ 25°C

VOC (Wt.%) Less than 2%; 20 g/L (California SCAQMD Method 316B)

Viscosity Not available

Vapor Pressure Less than 0.2 mm Hg
Vapor Density (Air=1) Approximately 3.
Evaporation Rate Not available.

10. STABILITY AND REACTIVITY

Stability Stable under recommended storage conditions.

Hazardous Polymerization Rapid exothermic polymerization will occur in the presence of water, amines

alkalis and alcohols.

Hazardous Decomposition Products Oxides of carbon. Oxides of nitrogen. Irritating vapors.

#### SUREHOLD. Low Odor, Low Blooming Cyanoacrylate Adhesive, SH-201

Revision 1 Revision Date 15-Jan-2015

Incompatible materials Water, amines, alkalis and alcohols. Conditions to Avoid Spontaneous polymerizations.

Hazardous Products of Combustion None.

#### 11. TOXICOLOGICAL INFORMATION

Product toxicity data

Acute oral LD50 greater than 5,000 mg/kg (rat) (estimated)

Acute dermal LD50 greater than 2000 mg/kg (rabbit) (estimated)

#### 12. ECOLOGICAL INFORMATION

No data available

#### 13. DISPOSAL CONSIDERATIONS

Recommended Method of

Disposal should be made in accordance with federal, state and local regulations.

Disposal

Not a RCRA hazardous waste.

#### 14. TRANSPORT INFORMATION

**DOT (49CFR 172)** 

#### US Department of Transportation - DOT - 49 CFR (Ground)

Proper Shipping Name Combustible liquids, n.o.s. (Cyanoacrylate ester)

Hazard Class 3 Packaging Group None UN/ID Number NA 1993 Marine pollutant None

Exceptions (Not more than 450 liters) Unrestricted

IATA (Air)

Proper Shipping Name Aviation regulated liquid n.o.s (Cyanoacrylate ester).

Class or Division Class 9 Packaging Group None

UN/ID Number UN 3334

Exceptions (Not more than 500 ml) Unrestricted

**IMDG (Vessel)** 

Proper Shipping Name Unrestricted

Hazard Class None Packaging Group None
UN Number None Marine pollutant None

Exceptions N/A

#### 15. REGULATORY INFORMATION

SARA Section 302 EHS None.

Sara Sections 311/312 Immediate Health Hazard, Delayed Health Hazard, Fire and Reactive.

Sara Section 313 This product contains the following toxic chemicals subject to the reporting

requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372): Methoxyethyl cyanoacrylate (CAS #27816-23-5).

California Proposition 65 No California Proposition 65 listed chemicals are known to be present.

TSCA 8 (b) Inventory Status All components of this product are listed (or exempt) on the EPA TSCA Inventory.

TSCA 12 (b) Export Notifications None.

Canada Regulatory Information All components are listed on or exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class B.3, D.2.B

#### SUREHOLD. Low Odor, Low Blooming Cyanoacrylate Adhesive, SH-201

Revision 1 Revision Date 15-Jan-2015

## 16. OTHER INFORMATION

Estimated HMIS HEALTH 2, FLAMMABILITY 2, REACTIVITY HAZARD 1 Classification

(HMIS is a registered trademark of the National Paint and Coatings Association)

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication; however, no guarantee is made to it accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.